






TRUMPF seam lockers

Electric power tools for sheet metal processing

	 TruTool F 300 Description	 TruTool F 300 with 1400 W motor Description	 TruTool F 301 Description	 TruTool F 305
Sheet thickness Steel 400 N / mm ² (min.) Steel 400 N / mm ² (max.)	0.75 mm 1.25 mm	0.75 mm 1.25 mm	0.45 mm 1 mm	0.45 mm 0.75 mm
Working speed	4-7 m/min.	6.5-10.5 m/min.	4-6 m/min.	4-7 m/min.
Smallest radius	150 mm inner radius 300 mm outer radius	150 mm inner radius 300 mm outer radius	150 mm inner radius 300 mm outer radius	--
Weight	5.4 kg	6.2 kg	5.2 kg	5.2 kg

	 TruTool F 125 Description	 TruTool F 140 Description	 TruTool F 140 for fan blower long flange / short flange Description
Sheet thickness Steel 400 N / mm ² (max.) Steel 600 N / mm ² (max.)	1.25mm	1.4 mm 0.6 mm	Long 1.4 mm 0.6 mm Short 0.75 mm 0.6 mm
Working speed	5-6 m/min.	6-10 m/min.	6-10 m/min.
Smallest radius	-	300 mm inner radius 500 mm outer radius	300 mm inner radius 100 mm outer radius
Weight	2.8 kg	4.2 kg	4.2 kg